


# Inch RMS Series



выбирать	Расследование	No.	Size										Rated load(N)	
			Д		Д		Б		Shielded Type		Chamfering		Kp	Cor
			mm	inch	mm	inch	Open Type		Shielded Type		rsmm (r)			
							mm	inch	mm	inch	mm	inch		
RMS4	12.7	0.5	41.28	1.625	15.875	0.625	15.875	0.625	1	0.0039	7350	4410	0.1076	
RMS5	15.875	0.625	46.04	1.8126	15.875	0.625	15.875	0.625	1	0.0039	9880	6200	0.1172	
RMS6	19.05	0.75	50.8	2	17.46	0.6874	17.46	0.6874	1	0.0039	10450	6560	0.1606	
RMS7	22.225	0.875	57.15	2.25	17.46	0.6874	17.46	0.6874	1.1	0.0043	10780	6980	0.223	
RMS8	25.4	1	63.5	2.5	19.5	0.75	19.5	0.75	1.1	0.0043	17220	11390	0.259	
RMS9	28.575	1.125	71.44	2.8126	20.64	0.8126	20.64	0.8126	1.1	0.0043	22840	15680	0.372	
RMS10	31.75	1.25	79.37	3.125	22.23	0.8752	22.23	0.8752	1.1	0.0043	26700	17570	0.542	
RMS11	34.925	1.375	88.9	3.5	22.23	0.8752	22.23	0.8752	1.5	0.059	28400	20900	0.7	
RMS12	38.1	1.5	95.25	3.75	23.81	0.9374	23.81	0.9374	1.5	0.059	31390	22380	0.8	