


1600 Series



выбирать		Расследование	No.	Size										Rated load(N)		Bec (кг)
				Д		Д		Б		Chamfering		Kp	Cor			
				mm	inch	mm	inch	Open Type		Shielded Type				rsmin (r)		
								mm	inch	mm	inch			mm	inch	
1601	4.762	0.1875	17.462	0.6875	6.35	0.25	7.938	0.3125	0.3	0.012	1970	730	0.007			
1602	6.35	0.25	17.462	0.6875	6.35	0.25	7.938	0.3125	0.3	0.012	1970	730	0.0065			
1603	7.938	0.3125	22.225	0.875	7.144	0.2813	8.731	0.3437	0.3	0.012	3290	1360	0.012			
1604	9.525	0.375	22.225	0.875	7.144	0.2813	8.731	0.3437	0.4	0.016	3330	1410	0.0105			
1605	7.938	0.3125	23.019	0.9063	7.938	0.3125	7.938	0.3125	0.3	0.012	3330	1410	0.016			
1606	9.525	0.375	23.019	0.9063	7.938	0.3125	7.938	0.3125	0.4	0.016	3330	1410	0.015			
1607	11.112	0.4375	23.019	0.9063	7.938	0.3125	7.938	0.3125	0.4	0.016	2690	1270	0.015			
1614	9.525	0.375	28.575	1.125	9.525	0.375	9.525	0.375	0.6	0.024	5110	2390	0.03			
1615	11.112	0.4375	28.575	1.125	9.525	0.375	9.525	0.375	0.6	0.024	5110	2390	0.028			
1616	12.7	0.5	28.575	1.125	9.525	0.375	9.525	0.375	0.6	0.024	5110	2390	0.026			
1620	11.112	0.4375	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.05			
1621	12.7	0.5	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.048			
1622	14.288	0.5625	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.046			
1623	15.875	0.625	34.925	1.375	11.112	0.4375	11.112	0.4375	0.6	0.024	7450	3700	0.041			
1628	15.875	0.625	41.275	1.625	12.7	0.5	12.7	0.5	0.6	0.024	9390	5020	0.072			
1630	19.05	0.75	41.275	1.625	12.7	0.5	12.7	0.5	0.6	0.024	9390	5020	0.069			
1633	15.875	0.625	44.45	1.75	12.7	0.5	12.7	0.5	0.6	0.024	9390	5020	0.092			
1635	19.05	0.75	44.45	1.75	12.7	0.5	12.7	0.5	0.6	0.24	9390	5020	0.09			
1638	19.05	0.75	50.8	2	14.288	0.5625	14.288	0.5625	0.9	0.035	10060	5860	0.145			
1640	22.225	0.875	50.8	2	14.288	0.5625	14.288	0.5625	0.9	0.035	10060	5860	0.133			
1641	25.4	1	50.8	2	14.288	0.5625	14.288	0.5625	0.9	0.035	10060	5860	0.121			
1652	28.575	1.125	63.5	2.5	15.875	0.625	15.875	0.625	0.9	0.035	19460	11310	0.211			
1654	31.75	1.25	63.5	2.5	15.875	0.625	15.875	0.625	0.9	0.035	19460	11310	0.193			
1657	31.75	1.25	65.087	2.5625	17.462	0.6875	17.462	0.6875	0.9	0.035	19460	11310	0.232			
1658	33.337	1.3125	65.087	2.5625	17.462	0.6875	17.462	0.6875	0.9	0.035	19460	11310	0.21			