


6000 Series



выбирать		Расследование	No.	Size										Rated load(N)		Bec (кг)
				Д		Д		Б		Chamfering		Kp	Cor			
				mm	inch	mm	inch	Open Type		Shielded Type				rsmin (r)		
								mm	inch	mm	inch			mm	inch	
603	3	0.1181	9	0.3543	3	0.1181	5	0.1181	0.2	0.008	486	223	0.0014			
604	4	0.1575	12	0.4724	4	0.1575	4	0.1575	0.2	0.008	960	350	0.0023			
605	5	0.1969	14	0.5512	5	0.1969	5	0.1969	0.2	0.008	1070	420	0.0037			
606	6	0.2362	17	0.6693	6	0.2362	6	0.2362	0.3	0.012	1960	730	0.0069			
607	7	0.2756	19	0.748	6	0.2362	6	0.2362	0.3	0.012	2800	1060	0.0082			
608	8	0.315	22	0.8661	7	0.2756	7	0.2756	0.3	0.012	3290	1360	0.0129			
609	9	0.3543	24	0.9449	7	0.2756	7	0.2756	0.3	0.012	3330	1410	0.016			
6000	10	0.3937	26	1.0236	8	0.315	8	0.315	0.3	0.012	4160	1780	0.019			
6001	12	0.4724	28	1.1024	8	0.315	8	0.315	0.3	0.012	5110	2380	0.022			
6002	15	0.5906	32	1.2598	9	0.3543	9	0.3543	0.3	0.012	5590	2840	0.03			
6003	17	0.6693	35	1.378	10	0.3937	10	0.3937	0.3	0.012	6000	3250	0.039			
6004	20	0.7874	42	1.6535	12	0.4724	12	0.4724	0.6	0.024	9390	5020	0.069			
6005	25	0.9843	47	1.8504	12	0.4724	12	0.4724	0.6	0.024	10060	5860	0.08			
6006	30	1.1811	55	2.1654	13	0.5118	13	0.5118	1	0.039	11900	7460	0.116			
6007	35	1.378	62	2.4409	14	0.5512	14	0.5512	1	0.039	16210	10420	0.115			
6008	40	1.5748	68	2.6677	15	0.5906	15	0.5906	1	0.039	17030	11700	0.192			
6009	45	1.7717	75	2.9528	16	0.6299	16	0.6299	1	0.039	21080	14780	0.245			
6010	50	1.9685	80	3.1496	16	0.6299	16	0.6299	1	0.039	22000	16260	0.261			
60/22	22	0.8661	44	1.7323	12	0.4724	12	0.4724	0.6	0.024	9400	5050	0.074			
60/28	28	1.1024	52	2.0472	12	0.4724	12	0.4724	0.6	0.024	12500	7400	0.098			
60/32	32	1.2598	58	2.2835	13	0.5118	13	0.5118	1	0.039	15100	9150	0.129			