


N2200 Series



| выбирать | Раследование | Обозначение | Основные размеры (мм) | | | | | Базовая грузоподъемность (кН) | | Ограниченная скорость (об/мин) | Масса (кг) | |
|----------|--------------|-------------|-----------------------|-----|----|-----------|--------|-------------------------------|-------------------|--------------------------------|------------|-------|
| | | | д | Д | Б | рупий мин | rs1min | Динамический (Cr) | Статический (Cor) | Смазка Масло | | |
| | | N2208 | 40 | 80 | 23 | 1.1 | 1.1 | 58 | 62 | 8500 | 10000 | 0.48 |
| | | N2209 | 45 | 85 | 23 | 1.1 | 1.1 | 61.5 | 68 | 7600 | 9000 | 0.52 |
| | | N2210 | 50 | 90 | 23 | 1.1 | 1.1 | 64 | 73.5 | 6900 | 8100 | 0.56 |
| | | N2211 | 55 | 100 | 25 | 1.5 | 1.1 | 75.5 | 87 | 6300 | 7400 | 0.758 |
| | | N2212 | 60 | 110 | 28 | 1.5 | 1.5 | 96 | 116 | 5800 | 6800 | 1.04 |
| | | N2213 | 65 | 120 | 31 | 1.5 | 1.5 | 120 | 149 | 5400 | 6300 | 1.37 |
| | | N2214 | 70 | 125 | 31 | 1.5 | 1.5 | 119 | 151 | 5000 | 5900 | 1.44 |
| | | N2215 | 75 | 130 | 31 | 1.5 | 1.5 | 130 | 162 | 4700 | 5500 | 1.52 |
| | | N2216 | 80 | 140 | 33 | 2 | 2 | 147 | 186 | 4400 | 5100 | 1.89 |
| | | N2217 | 85 | 150 | 36 | 2 | 2 | 170 | 218 | 4100 | 4800 | 2.39 |
| | | N2218 | 90 | 160 | 40 | 2 | 2 | 197 | 248 | 3900 | 4600 | 3.04 |
| | | N2219 | 95 | 170 | 43 | 2.1 | 2.1 | 230 | 298 | 3600 | 4300 | 3.71 |
| | | N2220 | 100 | 180 | 46 | 2.1 | 2.1 | 258 | 340 | 3500 | 4100 | 4.48 |
| | | N2222 | 110 | 200 | 53 | 2.1 | 2.1 | 320 | 415 | 3100 | 3700 | 6.43 |
| | | N2224 | 120 | 215 | 58 | 2.1 | 2.1 | 350 | 460 | 2900 | 3400 | 8.03 |
| | | N2226 | 130 | 230 | 64 | 3 | 3 | 380 | 530 | 2600 | 3100 | 10 |
| | | N2228 | 140 | 250 | 68 | 3 | 3 | 445 | 635 | 2400 | 2800 | 12.6 |
| | | N2230 | 150 | 270 | 73 | 3 | 3 | 500 | 710 | 2200 | 2600 | 16 |