


## 67 Super Thin Series



| выбирать      |    | Bearing<br>NO. | Shape Dimension |         |       |         |       |         |           |             | Basic Load Rating(N) |                      | Масса<br>(кг) |
|---------------|----|----------------|-----------------|---------|-------|---------|-------|---------|-----------|-------------|----------------------|----------------------|---------------|
| Расследование |    |                | d(mm)           | d(inch) | D(mm) | D(inch) | B(mm) | B(inch) | r min(mm) | r min(inch) | Динамический(Cr)     | Статический<br>(Cor) |               |
| 6700          | 10 | 0.3937         | 15              | 0.5906  | 4     | 0.1575  | 0.1   | 0.0039  | 800       | 390         | 0.0019               |                      |               |
| 6701          | 12 | 0.4724         | 18              | 0.7087  | 4     | 0.1575  | 0.2   | 0.0079  | 910       | 530         | 0.0031               |                      |               |
| 6702          | 15 | 0.5906         | 21              | 0.8268  | 4     | 0.1575  | 0.2   | 0.0079  | 850       | 490         | 0.0036               |                      |               |
| 6703          | 17 | 0.6693         | 23              | 0.9055  | 4     | 0.1575  | 0.2   | 0.0079  | 960       | 610         | 0.0040               |                      |               |
| 6704          | 20 | 0.7874         | 27              | 1.0630  | 4     | 0.1575  | 0.2   | 0.0079  | 1030      | 720         | 0.0059               |                      |               |
| 6705          | 25 | 0.9843         | 32              | 1.2598  | 4     | 0.1575  | 0.2   | 0.0079  | 1090      | 830         | 0.0070               |                      |               |
| 6706          | 30 | 1.1811         | 37              | 1.4567  | 4     | 0.1575  | 0.2   | 0.0079  | 1170      | 980         | 0.0083               |                      |               |
| 6707          | 35 | 1.3780         | 44              | 1.7323  | 5     | 0.1969  | 0.3   | 0.0118  | 1850      | 1630        | 0.0150               |                      |               |
| 6708          | 40 | 1.5748         | 50              | 1.9685  | 6     | 0.2362  | 0.3   | 0.0118  | 2519      | 2234        | 0.0230               |                      |               |
| 6709          | 45 | 1.7717         | 55              | 2.1654  | 6     | 0.2362  | 0.3   | 0.0118  | 2577      | 2401        | 0.0250               |                      |               |
| 6710          | 50 | 1.9685         | 62              | 2.4409  | 6     | 0.2362  | 0.3   | 0.0118  | 2666      | 2636        | 0.0340               |                      |               |